

Safety Data Sheet

LOCTITE SI 598 BK RTV SILICON known as Loctite 598 Black 95G AU

Page 1 of 9 SDS No.: 152851

V001.4

Date of issue: 16.07.2021

Section 1. Identification of the substance/preparation and of the company/undertaking

Product name: LOCTITE SI 598 BK RTV SILICON known as Loctite 598 Black 95G AU

Intended use: Silicone sealant

Supplier:

Henkel Australia Pty Ltd 135-141 Canterbury Road Kilsyth, Victoria, 3137 Australia

Phone: +61 (3) 9724 6444

Emergency information: 24 HOUR EMERGENCY CONTACT NUMBER: 1800 032 379

Section 2. Hazards identification

Classification of the substance or mixture

Hazardous according to the criteria of Safe Work Australia.

GHS Classification:

Hazard Class Hazard Category

Serious eye damage/eye irritation Category 1
Skin sensitizer Category 1
Chronic hazards to the aquatic Category 3

environment

Hazard pictogram:



Signal word: Danger

LOCTITE SI 598 BK RTV SILICON known as Loctite

598 Black 95G AU

Hazard statement(s): H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H412 Harmful to aquatic life with long lasting effects.

Precautionary Statement(s):

Prevention: P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P272 Contaminated work clothing should not be allowed out of the workplace.

P273 Avoid release to the environment.

P280 Wear protective gloves, eye protection, and face protection.

Response: P302+P352 IF ON SKIN: Wash with plenty of water.

P305+P351+P338+P315 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to remove. Continue rinsing. Get immediate

medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

Disposal: P501 Dispose of contents/container to an appropriate treatment and disposal facility in

accordance with applicable laws and regulations.

Dangerous Goods information:

Not classified as Dangerous Goods according to the criteria of the Australian Code for the Transport of Dangerous Goods by Road and Rail (ADG Code).

Section 3. Composition / information on ingredients

General chemical description: Mixture

resins

Type of preparation: Silicone sealant

Identity of ingredients:

Chemical ingredients	CAS-No.	Proportion
Limestone	1317-65-3	30- < 60 %
Silane, dichlorodimethyl-, reaction products with	68611-44-9	< 10 %
silica		
Butan-2-one O,O',O"-(vinylsilylidyne)trioxime	2224-33-1	3- < 10 %
Butan-2-one O,O',O",O"-silanetetrayltetraoxime	34206-40-1	< 1 %
non hazardous ingredients~		30- <= 60 %

Section 4. First aid measures

Ingestion: Rinse mouth, do not induce vomiting, consult a doctor.

Skin: Immediately wash skin thoroughly with soap and water.

Seek medical advice.

Eyes: Immediately flush eyes with plenty of water for at least 15 minutes.

Immediate medical treatment necessary.

Inhalation: Move to fresh air. If symptoms persist, seek medical advice.

First Aid facilities: Eye wash

Normal washroom facilities

LOCTITE SI 598 BK RTV SILICON known as Loctite

598 Black 95G AU

Medical attention and special

treatment:

Treat symptomatically.

Section 5. Fire fighting measures

Suitable extinguishing media: Carbon dioxide, foam, powder

Water spray or fog.

Improper extinguishing media: High pressure waterjet

Decomposition products in case of

fire:

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

Oxides of carbon. Oxides of silicon.

Special protective equipment for

fire-fighters:

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional fire fighting advice: In case of fire, keep containers cool with water spray.

Collect contaminated fire fighting water separately. It must not enter drains.

Section 6. Accidental release measures

Personal precautions: Use personal protective equipment as described in Section 8.

Avoid contact with skin and eyes.

Environmental precautions: Do not empty into drains / surface water / ground water.

Clean-up methods: Absorb spill with inert material. Shovel material into appropriate container for disposal.

Dispose of contaminated material as waste according to Section 13.

Section 7. Handling and storage

Precautions for safe handling: Avoid skin and eye contact.

Refer to Section 8.

Ensure that workrooms are adequately ventilated.

Conditions for safe storage: Suitable material for containers: original container.

Store in a cool, dry, well-ventilated area. Keep away from heat and direct sunlight.

Section 8. Exposure controls / personal protection

${\bf National\ exposure\ standards:}$

In gredient [Regulated substance]	form of	TWA (ppm)	TWA	Peak Limit.		STEL (ppm)	STEL
	exposure		(mg/m3)	(ppm)	(mg/m3)		(mg/m3)
Nuisance dusts, inhalable dust 1317-65-3	Inhalable dust.		10				
Nuisance dusts, inhalable dust 68611-44-9	Inhalable dust.		10				
Fumed silica (respirable dust)	Respirable		2				
68611-44-9	dust.						

Page 4 of 9

SDS No.: 152851 V001.4

LOCTITE SI 598 BK RTV SILICON known as Loctite

598 Black 95G AU

Silica, Amorphous: Fumed silica	Respirable	2		
(respirable dust)	dust.			
68611-44-9				

Engineering controls: Ensure good ventilation/suction at the workplace.

Eye protection: Wear chemical goggles and face shield.

Skin protection: Use of an impervious apron is recommended.

Suitable protective gloves.

Please note that in practice the working life of chemical resistant gloves may be considerably reduced as a result of many influencing factors (e.g. temperature). Suitable risk assessment should be carried out by the end user. If signs of wear and tear are noticed

then the gloves should be replaced.

Respiratory protection: If inhalation risk exists, wear a respirator or air supplied mask complying with the

requirements of AS/NZS 1715 and AS/NZS 1716.

Section 9. Physical and chemical properties

Appearance: Black **Odor:** mild

Melting point / freezing point: Not available.

Specific gravity: 1.3

Flash point: $> 93 \,^{\circ}\text{C} (> 199.4 \,^{\circ}\text{F})$

(Tagliabue closed cup)

Vapor pressure: < 5 mm hg

(; 20 °C (68 °F))

Vapor density: Heavier than air. **Density:** 1.05 g/cm3

Solubility in water: Polymerises in presence of water.

VOC content:

(2010/75/EC)

Section 10. Stability and reactivity

Stability: Stable under recommended storage conditions.

< 5.00 %

Conditions to avoid: Exposure to air or moisture over prolonged periods.

Incompatible materials: Strong oxidizing agents.

Reaction with acids: production of heat and carbon dioxide.

Hazardous decomposition

products:

In case of fire toxic gases can be released.

Oxides of carbon.

Oxides of silicon.

Hazardous polymerization: Will not occur.

Section 11. Toxicological information

LOCTITE SI 598 BK RTV SILICON known as Loctite

598 Black 95G AU

Health Effects:

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Skin: Mild skin irritation.

Symptoms may include redness, edema, drying, defatting and cracking of the skin.

May cause an allergic skin reaction.

Eyes: Causes serious eye damage.

Contact with the eyes may cause moderate to severe eye injury. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with

marked redness and swelling of the conjunctiva.

Inhalation: May cause irritation to nose and throat.

Acute toxicity:

Hazardous components	Value	Value	Route of	Exposure	Species	Method
CAS-No.	type		application	time		
Limestone	LD50	$> 5,000 \mathrm{mg/kg}$	oral		rat	not specified
1317-65-3	LD50	> 5,000 mg/kg			rat	not specified
			dermal			_
Silane, dichlorodimethyl-,	LD50	> 5,000 mg/kg	oral		rat	not specified
reaction products with	LD50	$> 2,000 \mathrm{mg/kg}$			rat	not specified
silica			dermal			
68611-44-9						
Butan-2-oneO,O',O"-	LD50	> 2,000 mg/kg	oral		rat	OECD Guideline 425 (Acute
(vinylsilylidyne)trioxime	Acute	2,500 mg/kg	oral			Oral Toxicity: Up-and-Down
2224-33-1	toxicity	> 2,009 mg/kg			rat	Procedure)
	estimate		dermal			Expert judgement
	(ATE)					OECD Guideline 402 (Acute
	LD50					Dermal Toxicity)
Butan-2-one O,O',O",O"-	LD50	2,463 mg/kg	oral		rat	OECD Guideline 401 (Acute
silanetetrayltetraoxime	LD50	$> 2,000 \mathrm{mg/kg}$			rat	Oral Toxicity)
34206-40-1			dermal			OECD Guideline 402 (Acute
						Dermal Toxicity)

Skin corrosion/irritation:

Hazardous components CAS-No.	Result	Exposure time	Species	Method
Limestone 1317-65-3	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	not irritating	4 h	rabbit	not specified
But an-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

Hazardous components	Result	Exposure	Species	Method
CAS-No.		time		
Limestone 1317-65-3	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	not irritating		rabbit	not specified
Butan-2-one O,O',O'',O''- silanete trayltetraoxime 34206-40-1	irritating	1 h	rabbit	OECD Guideline 405 (Acute Eye Irritation/Corrosion)

LOCTITE SI 598 BK RTV SILICON known as Loctite 598 Black 95G AU

Respiratory or skin sensitization:

Hazardous components CAS-No.	Result	Test type	Species	Method
Limestone 1317-65-3	not sensitising	Mouse local lymphnod e assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	not sensitising	Patch-Test	human	human repeat insult patch test
Butan-2-one O,O',O'- (vinylsilylidyne)trioxime 2224-33-1	Sensitizing	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Butan-2-one O,O',O'',O''-silanetet rayltetraoxime 34206-40-1	sensitising	Guinea pig maximisat ion test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

Hazardous components	Result	Type of study/	Metabolic	Species	Method
CAS-No.		Route of administration	activation/		
Time			Exposure time		OECD Guideline 471
Limestone	negative	bacterial reverse	with and without		
1317-65-3	negative	mutation assay (e.g	with and without		(Bacterial Reverse Mutation
	negative	Ames test)	with and without		Assay)
		in vitro mammalian			OECD Guideline 473 (In vitro
		chromosome			Mammalian Chromosome
		aberration test			Aberration Test)
		mammalian cell			OECD Guideline 476 (In vitro
		gene mutation assay			Mammalian Cell Gene
					Mutation Test)
Silane, dichlorodimethyl-,	negative	bacterial reverse	with and without		Ames Test
reaction products with	negative	mutation assay (e.g	with and without		Chromosome Aberration Test
silica		Ames test)			
68611-44-9		in vitro mammalian			
		chromosome			
		aberrationtest			
Butan-2-one O,O',O"-	negative	bacterial reverse	with and without		OECD Guideline 471
(vinylsilylidyne)trioxime		mutation assay (e.g			(Bacterial Reverse Mutation
2224-33-1		Ames test)			Assay)
Butan-2-one O,O',O''-	negative	intraperitoneal		mouse	OECD Guideline 474
(vinylsilylidyne)trioxime					(Mammalian Erythrocyte
2224-33-1					Micronucleus Test)

Repeated dose toxicity:

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Method
Limestone 1317-65-3	NOAEL=1,000 mg/kg	oral: gavage	48 ddaily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	NOAEL=500 mg/kg	oral: feed	5-8 wdaily	rat	not specified
Butan-2-one O,O',O'- (vinylsilylidyne)trioxime 2224-33-1	LOAEL=40 mg/kg	oral: gavage	13 w5 d/week	rat	EPA OPPTS 870.3100 (90- Day Oral Toxicity in Rodents)
Butan-2-one O,O',O'',O''-silanetetrayltetraoxime 34206-40-1	NOAEL=25 mg/kg	oral: drinking water	90 ddaily: ad libitum	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Section 12. Ecological information

LOCTITE SI 598 BK RTV SILICON known as Loctite 598 Black 95G AU

General ecological information: Do not empty into drains / surface water / ground water.

Ecotoxicity: Harmful to aquatic life.

Toxicity:

Hazardous components CAS-No.	Value type	Value	Acute Toxicity Study	Exposure time	Species	Method
Limestone 1317-65-3	LC50	> 10,000 mg/l	Fish	96 h	not specified	OECD Guideline 203 (Fish, Acute
Limestone 1317-65-3	EC50	> 1,000 mg/l	Daphnia	48 h	Daphnia magna	Toxicity Test) OECD Guideline 202 (Daphnia sp.
T	EGGO	200 4	.,	72.1		Acute Immobilisation Test)
Limestone 1317-65-3	EC50	> 200 mg/l	Algae	72 h	not specified	OECD Guideline 201 (Alga, Growth Inhibition Test)
Limestone 1317-65-3	EC50	> 1,000 mg/l	Bacteria	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	LC50	> 10,000 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	Inhibition Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
Silane, dichlorodimethyl-, reaction products with silica 68611-44-9	EC50	> 10,000 mg/l	Daphnia	24 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation
Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	LC50	> 560 mg/l	Fish	96 h	Brachydanio rerio (new name: Danio rerio)	Test) OECD Guideline 203 (Fish, Acute Toxicity Test)
But an-2-one O,O',O''- (vinylsilylidyne)trioxime	NOEC	50 mg/l	Fish	14 d	Oryzias latipes	OECD Guideline 204 (Fish,
2224-33-1 Butan-2-one O,O',O"- (vinylsilylidyne)trioxime 2224-33-1	EC50	201 mg/l	Daphnia	48 h	Daphnia magna	Prolonged Toxicity Test: 14-day Study) OECD Guideline 202 (Daphnia sp. Acute Immobilisation
But an-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	EC50	94 mg/l	Algae	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	Test) OECD Guideline 201 (Alga, Growth Inhibition Test)
But an-2-one O,O',O''- (vinylsilylidyne)trioxime	NOEC	30 mg/l	Algae	72 h	Selenastrum capricornutum (newname: Pseudokirchneriella	OECD Guideline 201 (Alga, Growth
2224-33-1 Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime	LC50	843 mg/l	Fish	96 h	subcapitata) Pimephales promelas	Inhibition Test) OECD Guideline 203 (Fish, Acute
34206-40-1 Butan-2-one O,O',O'',O''- silanetetrayltetraoxime 34206-40-1	NOEC	50 mg/l	Fish	14 d	Oryzias latipes	Toxicity Test) OECD Guideline 204 (Fish, Prolonged Toxicity
Butan-2-one O,O',O'',O''-silanetetrayltetraoxime 34206-40-1	EC50	201 mg/l	Daphnia	48 h	Daphnia magna	Test: 14-day Study) OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butan-2-one O,O',O",O"-silanetetrayltetraoxime 34206-40-1	EC50	16 mg/l	Algae	72 h	Selenastrum capricornutum (newname: Pseudokirchneriella subcapitata)	OECD Guideline
Butan-2-one O,O',O'',O''- silanetetrayltetraoxime 34206-40-1	NOEC	2.6 mg/l	Algae	72 h	subcapitata) Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline

$\label{persistence} \textbf{Persistence and degradability:}$

Hazardous components	Result	Route of	Degradability	Method
CAS-No.		application		

Page 8 of 9

SDS No.: 152851 V001.4

LOCTITE SI 598 BK RTV SILICON known as Loctite 598 Black 95G AU

Butan-2-one O,O',O''- (vinylsilylidyne)trioxime 2224-33-1	not readily biodegradable.	aerobic	26 %	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
* * *	not readily biodegradable.	aerobic	28 %	OECD Guideline 301 C (Ready
silanetetrayltetraoxime 34206-40-1				Biodegradability: Modified MITI Test (I))

Section 13. Disposal considerations

Waste disposal of product: Collection and delivery to recycling enterprise or other registered elimination institution.

Dispose of as hazardous waste in compliance with local and national regulations.

Disposal for uncleaned package: After use, tubes, cartons and bottles containing residual product should be disposed of as

chemically contaminated waste in an authorised legal land fill site or incinerated.

Section 14. Transport information

Road and Rail Transport:

Dangerous Goods information: Not classified as Dangerous Goods according to the criteria of the

Australian Code for the Transport of Dangerous Goods by Road and

Rail (ADG Code).

Marine transport IMDG:

Not dangerous goods

Air transport IATA:

Not dangerous goods

Section 15. Regulatory information

SUSMP Poisons Schedule None

AIIC: All components are listed or are exempt from listing on the Australian Inventory of

Chemical Substances (AICIS).

Section 16. Other information

Abbreviations/acronyms: ADGC - Australian Dangerous Goods Code

STEL - Short term exposure limit TWA - Time weighted average

AIIC - Australian Inventory of Industrial Chemicals (AIIC) AICIS - Australian Industrial Chemicals Introduction Scheme

Reason for issue: Reviewed SDS. Reissued with new date. involved chapters: 1 - 16

Page 9 of 9

SDS No.: 152851 V001.4

LOCTITE SI 598 BK RTV SILICON known as Loctite 598 Black 95G AU

Date of previous issue: 29.07.2016

Disclaimer:

The percentage weight (% w/w) of ingredients is not to be taken as a specification guaranteed by Henkel Australia Pty. Limited, but only as an approximate guide to the content of hazardous ingredients in the material. The information contained herein does not constitute a guarantee by Henkel Australia Pty. Limited concerning the properties of the material

The information contained in the Safety Data Sheet is offered in good faith and has been developed from what is believed to be accurate and reliable sources. The information is offered without warranty, representation, inducement or licence and Henkel Australia Pty. Limited assumes no legal responsibility for reliance upon same. Henkel Australia Pty. Limited disclaims any liability for loss, injury or damage incurred in connection with the use of the material or its associated Safety Data Sheet.

This information is not to be construed as a representation that the material is suitable for any particular purpose or use except those conditions and warranties implied by either Commonwealth or State statutes. Customers are encouraged to make their own enquiries as to the material's characteristics and, where appropriate, to conduct their own tests in the specific context of the material's intended use.

No warranty or representation of any kind is given with respect to the substantive or export laws of any other jurisdiction or country. Please confirm that the information provided herein conforms to the substantive export or other law of any other jurisdiction prior to export. Please contact Henkel Product Safety and Regulatory Affairs for additional assistance.